


To Splice or Not to splice... (N+1)xHR, OCxCPS Integrated Solutions

For Co-Pumped Laser Designs

ITF Technologies' Integrated Solutions provide a very efficient option for fiber laser manufacturing. They combine our efficient pump combiners with our high performance FBG High Reflector without any splice between the two. The Integrated Solution improves reliability and can decrease your integration time by removing the need to do the critical splice between the combiner and the FBG Mirror.

This combined solution will streamline the choice of components and will group them under the same product code number. The specification of the Central Wavelength of the HR and OC are tightened so that FBG pairs are always matching. This reduces the component management complexity during assembly.



KEY FEATURES

High Power Transfer Efficiency

Wavelength Insensitive

Custom Configurations Available

ROHS Compliant

APPLICATIONS

Fiber Lasers

Fiber Laser Combination

kW Class Fiber Lasers

Industrial & Research

FOR MORE INFO

Please contact us at:

North America: **514.748.4848**

888.922.1044

Europe: **+33 (0) 1 69 80 57 50**

Asia: **+86 755 2671 0449**

or via e-mail at: **info@itftechnologies**

(N + 1)xHR, OCxCPS
Integrated Solutions

FOR OPTIMUM CO-PUMPED LASER DESIGNS

(N + 1)xHR

PRODUCT CODE	CONFIGURATION	PUMP FIBER	SIGNAL FIBER	OUTPUT FIBER	POWER HANDLING (PUMPS)	POWER HANDLING (SIGNAL)
TFBG410C9117	7x1 + HR	106.5/125 0.22	n/a	20/400 um NA=0.06/0.46	200 W/port	1400 W
TFBG410C9118	7x1 + HR	200/220 um NA=0.22	n/a	20/400 um NA=0.06/0.46	200 W/port	1400 W
TFBG410C9119	7x1 + HR	220/242 um NA=0.22	n/a	20/400 um NA=0.06/0.46	200 W/port	1400 W
TFBG410C8989	(6+1)x1 + HR	106.5/125 0.22	10/125 um NA=0.08/0.46	20/400 um NA=0.06/0.46	150 W/port	900 W
√	(6+1)x1 + HR	200/220 0.22	10/125 um NA=0.08/0.46	20/400 um NA=0.06/0.46	200 W/port	1400 W
√	(6+1)x1 + HR	220/242 0.22	10/125 um NA=0.08/0.46	20/400 um NA=0.06/0.46	200 W/port	1400 W
TFBG410C8976	(6+1)x1 + HR	200/220 0.22	20/400 um NA=0.06/0.46	20/400 um NA=0.06/0.46	100 W/port	600 W
√	(6+1)x1 + HR	220/242 0.22	20/400 um NA=0.06/0.46	20/400 um NA=0.06/0.46	100 W/port	600 W

OCxCPS

PRODUCT CODE	CONFIGURATION	PUMP FIBER	SIGNAL FIBER	OUTPUT FIBER	POWER HANDLING (PUMPS)	POWER HANDLING (SIGNAL)
OCPS410C8990	OC + CPS	n/a	20/400 um NA=0.06/0.46	20/400 um NA=0.06/0.46	50 W	1000 W

√: Product available - product code not yet defined

ORDERING INFO

ITF Technologies inc.
400 Montpellier Blvd., Montreal, QC H4N 2G7
Tel: +1 514 748 4848
Fax: +1 514 744 2080
Toll Free: +1 888 922 1044
www.itftechnologies.com
info@itftechnologies.com

Customizable length between combiner and HR, or OC and CPS
Additional fiber configurations available

Typical power handling presented
Custom designs and prototypes also available